

TECHNICAL DATA SHEET



AEROSOLS



Maintenance & repair

WIKO® COOLING SPRAY FLAMMABLE

WIKO® COOLING SPRAY FLAMMABLE is used for a fast and effective cooling down of maximum -45 °C. The cooling spray enables a fast and easy error search in case of thermal disruptions.

- Mode of operation: cools down – freezes – shrinks
- High yield

Application areas

- Used to quickly and immediately cool down carburetors, injection systems, transistors and resistances
- Instant display of coldness after disconnection of a device
- Prevents heat exhaustion in the surroundings of soldering procedures
- Alleviates the fitting of bushes, bearings and axles into very narrow clearances
- Easy error search in case of thermal disruptions
Easy removing of chewing gum

Sizes / article number

400 ml can

AKSP.D400

Application

Spray the spots designated for cooling for a few seconds. The effect of coldness can be increased or decreased depending on the duration of spraying. Do not use the product for spots under pressure or stress. Do not spray onto body parts due to danger of freezing. The product is harmless if used in accordance with the instructions.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Safety data sheets

Please refer to the current data sheet for safety relevant data.

Click or scan here:



Member of

GLUETEC GROUP

GLUETEC Germany **wiko** WIKO Poland

GLUETEC Industrieklebstoffe GmbH & Co. KG
Am Biotop 8a
97259 Greußenheim - Germany
Tel: +49 (0) 9369 / 9836-0
info.de@gluetec-group.com
www.gluetec-group.com/de

WIKO KLEBETECHNIK Sp. z o.o.
ul. Ekonomiczna 8
42-271 Częstochowa – Poland
Tel: +48 (0) 34 372 58 58
info.pl@gluetec-group.com
www.gluetec-group.com/pl

TECHNICAL DATA SHEET

**Note:**

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.

Member of

GLUETEC GROUP

 GLUETEC Germany  WIKO Poland

GLUETEC Industrieklebstoffe GmbH & Co. KG
Am Biotop 8a
97259 Greußenheim - Germany
Tel: +49 (0) 9369 / 9836-0
info.de@gluetec-group.com
www.gluetec-group.com/de

WIKO KLEBETECHNIK Sp. z o.o.
ul. Ekonomiczna 8
42-271 Częstochowa – Poland
Tel: +48 (0) 34 372 58 58
info.pl@gluetec-group.com
www.gluetec-group.com/pl