

AEROSOLS



Application areas

- Automobile maintenance and repair
- Engineering and building sector
- Assembly and repair
- Shipping and oil production
- Power plants and chemical industry
- Heavy industry and mining

Application

Shake the can intensively before application and spray onto the area to be treated.

Maintenance and repair

WIKO® RUST-SHOCK

Immediate reaction based on a dual-effect: The special composition of the active substances causes a „cold shock“ on the corroded work piece.

WIKO® RUST SHOCK ingresses deeply in this process created smallest interspaces due to its high capillary action. Subsequently, the product dissolves the rust crystals and removes the connection between the rust layers.

- Super-fast loosening of rusty screws
- Free of silicone and grease
- Alcohol-based

Sizes / article number

400 ml can

AROS.D400

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

TECHNICAL DATA SHEET



Safety data sheets

Please refer to the current data sheet for safety relevant data.
Click or scan here:



Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.