

AEROSOLS



Surface protection and preparation **WIKO® ANTI RUST WAX**

WIKO® ANTI RUST WAX is used for the preservation of metals such as iron, steel, brass, tin, nickel, chromium and zinc as well as plastics. After drying, the product transforms into firmly adhering, tough-plastic, colorless and waterproof layer.

- Lasting conservation of metals and plastics
- Excellent suitability for surfaces coated with paint
- Good flow properties and durable protection against corrosion
- Can be easily removed with common solvents

Application areas

- Rust-proofing of plastics and metals like iron, steel, brass, tin, nickel, chromium, zinc, etc.
- Stockpiling / warehousing of tools
- Ocean transports
- Treatment of especially corrodible spots (welds, threads, screws, nuts, etc.)

Application

Clean the designated areas of dirt, rust, oil and grease before the application (we recommend a suited WIKO® cleaner, e.g. WIKO® INDUSTRIAL QUICK CLEANER art. no. 100134). Shake the aerosol can intensively for approx. 2 minutes and perform a test spraying. Apply the product crosswise from a distance of 20 to 30 cm and let the surfaces evaporate. WIKO® ANTI RUST WAX can be easily removed with common solvents.

Safety data sheets

Please refer to the current data sheet for safety relevant data.
Click or scan here:



Sizes / article number

400 ml can	100147
------------	--------

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

TECHNICAL DATA SHEET



Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.

Member of

GLUETEC GROUP

 GLUETEC Germany  WIKO Poland

GLUETEC Industrieklebstoffe GmbH & Co. KG
Am Biotop 8a
97259 Greußenheim - Germany
Tel: +49 (0) 9369 / 9836-0
info.de@gluetec-group.com
www.gluetec-group.com/de

WIKO KLEBETECHNIK Sp. z o.o.
ul. Ekonomiczna 8
42-271 Częstochowa – Poland
Tel: +48 (0) 34 372 58 58
info.pl@gluetec-group.com
www.gluetec-group.com/pl