

## AEROSOLS



## Spray paint & corrosion protection sprays **WIKO® ZINC REPAIR SPRAY**

WIKO® ZINC REPAIR SPRAY is a mixture of aluminum and zinc. The spray offers heat-resistant corrosion protection for many basic metals. Due to its color similarity with galvanized materials, it provides an optical compensation, whereby the resulting surface can be painted over easily.

- Fast-drying, smooth surface film that is free of pores
- High gloss level
- High resistance to abrasion
- Temperature range: to +200 °C (shortly up to +300 °C)

### Application areas

- Fast-drying protection against corrosion
- Perfect for repair of damaged zinc coatings
- Air conditioning and ventilation technology

### Sizes / article number

400 ml can                      AZAS.D400

### Application

Clean the designated surfaces completely of dirt, rust, oil and grease (we recommend the usage of a suited WIKO® cleaner, e.g. WIKO® INDUSTRIAL QUICK CLEANER art. No. AISR.D400). The application should be conducted at room temperature (approx. +16 °C to +25 °C). Shake the aerosol can intensively so that you can hear the ball inside for approx. 3 minutes. Perform a test spraying. Afterwards, apply the spray crosswise from a distance of 20 to 30 cm. The surface will be dust-dry after approx. 8 minutes, slip-proof after 20-25 minutes and thoroughly dried after approx. 24 hours. After usage, turn the aerosol can upside-down and spray until only propellant gas emerges.

### Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

# TECHNICAL DATA SHEET



## Safety data sheets

Please refer to the current data sheet for safety relevant data.

Click or scan here:



### Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.

**GLUETEC Industrieklebstoffe GmbH & Co. KG**  
Am Biotop 8a  
97259 Greußenheim - Germany  
Tel: +49 (0) 9369 / 9836-0  
info.de@gluetec-group.com  
www.gluetec-group.com/de

**WIKO KLEBETECHNIK Sp. z o.o.**  
ul. Ekonomiczna 8  
42-271 Częstochowa – Poland  
Tel: +48 (0) 34 372 58 58  
info.pl@gluetec-group.com  
www.gluetec-group.com/pl